

Identity - Tripoly Glaze KA

| | |
|--|---|
| SECTION I | |
| Manufacturers Name: Stevens Car Care Products, Inc. | Emergency Telephone Number: (440) 953-2900 |
| Address: 36542 Vine St. Eastlake, Ohio 44095 | Telephone Number for Information: (440) 953-2900 |
| | Date Prepared: 6/18/09 |
| | Signature of Preparer (optional) |

SECTION II - HAZARDOUS INGREDIENTS/Identity Information

| Hazardous Components (Specific Chemical Identity; Common Name(s)) | | | | | |
|---|-------------|-------------|--------------|-----------------------------|--------------|
| | | OSHA PEL | ACGIH TLV | Other Limits Recommended | % (Optional) |
| ALPHATIC HYDROCARBON | CAS. NO. | 8052-41-3 | 100 PPM | COMBUSTIBLE | |
| KEROSENE | CAS. NO. | 8008-20-6 | 100 PPM | COMBUSTIBLE | |
| DIMETHYLPOLYSILOXANE | CAS. NO. | 63148-82-9 | N/A | | |
| WATER | CAS. NO. | 7732-18-5 | N/A | | |
| CALCINED KAOLIN | CAS. NO. | 66402-28-1 | 10 MG/M3 | IRRITANT | |
| CARNAUBA WAX | CAS. NO. | N/A | | NONE | |
| | | | | | |
| | | | | | |
| | | | | | |

The precise composition of this mixture is proprietary information. A complete disclosure will be provided to a physician or nurse in the event of a medical emergency.

SECTION III - Physical/Chemical Characteristics

| | | | |
|-------------------------|------------|--------------------------------------|-----|
| Boiling Point | 212 F | Specific Gravity | < 1 |
| Vapor Pressure (mm Hg.) | N/A | Melting Point | |
| Vapor Density (AIR=1) | N/A | Evaporation Rate (Butyl Acetate = 1) | N/A |
| Solubility in Water | N/A | | |
| Appearance and Odor | TAN LIQUID | | |

SECTION IV - Fire and Explosion Hazard Data

| | | | |
|---|-------------------|------------|------------|
| Flash Point (Method Used) 200 F TOC | Flammable Liquids | LEL N/A | UEL N/A |
| Extinguishing Media Water, Fog, CO2 & Dry Chemicals | | | |
| Special Fire Fighting Procedures Wear full protective clothing, including helmet, self contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. | | | |
| Unusual Fire and Explosion Hazards This product is combustible at high temps. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. | | | |

Page 2

| | | | |
|---|--|-------------------------------|------------------------------------|
| SECTION V - Reactivity Data | | | |
| Stability | <input type="checkbox"/> Unstable | | Conditions to Avoid |
| | <input checked="" type="checkbox"/> Stable | | N/A |
| Incompatibility (Material to Avoid) STRONG OXIDIZERS, STRONG ACIDS | | | |
| Hazardous Decomposition or Byproducts OXIDES OR CARBON AND OTHER HAZARDOUS CHEMICALS. | | | |
| Hazardous Polymerization | <input type="checkbox"/> May Occur | | Conditions to Avoid |
| | <input checked="" type="checkbox"/> Will Not Occur | | N/A |
| SECTION VI - Health Hazard Data | | | |
| Route(s) of Entry | <input checked="" type="checkbox"/> Inhalation | <input type="checkbox"/> Skin | <input type="checkbox"/> Ingestion |
| Health Hazards (Acute and Chronic) N/A | | | |
| Carcinogenicity | NTP? | IARC Monographs? | OSHA Regulated? |
| Signs and Symptoms of Exposure May cause redness, tearing or blurring of vision. May cause skin irritation. May be irritating to the respiratory system. May cause irritation of the mucous membranes. | | | |
| Medical Conditions Generally Aggravated by Exposure | | | |
| Emergency and First Aid Procedures | | | |
| Eyes: | WASH WITH WATER FOR 15 MINUTES, LIFTING UPPER AND LOWER LIDS OCCASIONALLY. CALL A PHYSICIAN. | | |
| Skin: | WASH WITH SOAP AND WATER. IF IRRITATION PERSISTS, SEEK MEDICAL PHYSICIAN. | | |
| Inhalation: | MOVE TO FRESH AIR. | | |
| Ingestion: | DRINK TWO GLASSES OF WATER. DO NOT INDUCE VOMITING. CALL A PHYSICIAN. | | |
| SECTION VII - Precautions for Safe Handling and Use | | | |
| Steps to be Taken in Case Material is Released or Spilled REMOVE SOURCES OF IGNITION. BLOCK ANY POTENTIAL ROUTES TO WATER SYSTEM. | | | |

Waste Disposal Method
ABSORB SPILL WITH INERT MATERIAL. SHOVEL MATERIAL INTO APPROPRIATE CONTAINER FOR DISPOSAL.

Precautions to be Taken in Handling and Storing

SECTION VIII - Control Measures

Respiratory Protection (Specify Type)
N/A

| | | |
|-------------|------------------------|-----------|
| Ventilation | Local Exhaust - | Special - |
| | Mechanical (General) - | Other - |

| | |
|--|---|
| Protective Gloves IMPERVIOUS GLOVES | Eye Protection CHEMICAL SAFETY GOGGLES |
|--|---|

Other Protective Clothing or Equipment

Work/Hygenic Practices